

PRODUCT INFORMATION FOR TANKER VESSELS

NAVACLEAN 803 ALKATUFF PHS



HEAVY DUTY WATER BASED ALKALINE CLEANER AND DEGREASER. BASED ON STRONG ANIONIC SURFACE-ACTIVE AGENTS AND HIGH CONCENTRATION OF POTASSIUM SODIUM HYDROXIDE.

DESCRIPTION

- › For cleaning tanker vessels after Vegetable oils, animal oils, fatty acids, fish oils, greasers, waxes, oil, sludge, soot carbon deposits, and general dirt and grime
- › Can be discharged according to IMO MEPC.1/Circ. 590. and Marpol V
- › Concentrate that can be diluted with water for multiple cleaning purposes
- › Removes odors
- › Degreases multiple surfaces very efficiently, as high concentration of active ingredient

FEATURES

- › Strong alkaline cleaner
- › Water based cleaner
- › Efficiency enhanced by high quality surface-active agents
- › The product is biodegradable
- › Not harmful to the marine environment
- › Cleaning concentrate
- › Approved according to IMO MEPC.1/Circ. 590.
- › Complies to Marpol V

For detailed instructions on cargo hold cleaning please contact us at NAVADAN.
A range of support application equipment is also available.

NAVADAN

2630 Taastrup, Denmark
+45 49 17 03 57

navadan@navadan.com
navadan.com



DIRECTION FOR USE

General cleaning

- › Navaclean 803 can be applied by brush, spray, direct injection method or recirculation method. The recommended cleaning temperature ranges from ambient - 80°C and depends upon the type of cargo residues.
- › Direct injection method with tank washing machines: Dosage rate 10-50 liters per 1000 liters wash water. (1-5%)
- › Recirculation method: Use dosage rate of 20-50 liter per 1000 liter wash water
- › Spot cleaning: Hand spray 30-100% solution. Leave for approx. 30 minutes before rinsing with water.
- › We recommend using fresh water, but if not, feasible seawater can be used.

PRODUCT CHARACTERISTICS

Specific gravity:	1.1
Flash Point:	N/A
pH-value at 20°C:	>13

Corrosive action:

Metals: Avoid contact with aluminium, tin, zinc or their alloys.

Rubber: None

For risks and safety regulations, please see our Safety Data Sheet