

## PRODUCT INFORMATION

# NAVACLEAN 978 BAUXITE REMOVER



## ACID BASED BAUXITE REMOVER

### DESCRIPTION

- › Used for removing cementAn effective acid based liquid specifically blended to remove bauxite cargo deposits or bauxite stains
- › Available in 25/2007208 liter drums
- › Can be discharged according to Marpol V

### FEATURES

- › Removal of bauxite deposits and residues
- › Water-soluble and non-flammable liquid
- › Non harmful to the marine environment
- › Complies to Marpol V

For detailed instructions on cargo hold cleaning please contact us at NAVADAN.  
A range of support application equipment is also available.



## DIRECTION FOR USE

- › Preclean holds with high-pressure machine, in order to remove majority of bauxite deposits and ensure an effective cleaning operation with Navaclean 978.
- › Ensure that hold surfaces have dried, before applying the chemicals, in order to avoid unnecessary dilution.
- › Apply Navaclean 978 using spray equipment.

### Dosage:

- › Heavy Contamination: Undiluted
- › Light Contamination: 10-40%
- › After 15-30 minutes flush thoroughly with fresh water or high-pressure machine.
- › Directions are based on experience and are intended as a guide since conditions for each cleaning operation vary

## PRODUCT CHARACTERISTICS

|                         |              |
|-------------------------|--------------|
| Appearance:             | Clear liquid |
| Specific gravity:       | 1.15 at 20°C |
| Flash Point, PMCC:      | None         |
| pH-value (1% solution): | 1            |

### Corrosive Action:

|         |               |
|---------|---------------|
| Metals: | Slight action |
| Rubber: | None          |

For special risks and safety regulations, please see our Safety Data Sheet

The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.

