

PRODUCT INFORMATION FOR TANKER VESSELS

# NAVACLEAN 802 ALKATUFF SOFT



## STRONG WATER BASED ALKALINE CLEANER AND DEGREASER. BASED ON HIGH CONCENTRATION OF SODIUM HYDROXIDE.

### DESCRIPTION

- › Degreases multiple surfaces very efficiently, as high concentration of active ingredients
- › Removes odors
- › Concentrate that can be diluted with water for multiple cleaning purposes
- › Can be discharged according to IMO MEPC.1/Circ. 590. and Marpol V

### FEATURES

- › Strong alkaline cleaner
- › Water based cleaner
- › The product is biodegradable
- › Not harmful to the marine environment
- › Cleaning concentrate
- › Approved according to IMO MEPC.1/Circ. 590
- › Complies to Marpol V

For detailed instructions on cargo hold cleaning please contact us at NAVADAN.  
A range of support application equipment is also available.

**NAVADAN**

2630 Taastrup, Denmark  
+45 49 17 03 57

navadan@navadan.com  
navadan.com



## SPECIFICATIONS

- › Vegetable oils
- › Animal oils
- › Fatty acids
- › Fish oils
- › Greases
- › Waxes
- › Oil
- › Sludge,
- › Soot, carbon deposits
- › General dirt and grime.
- › Tested and approved by coating manufacturers.
- › Safe to use on epoxy coatings, polyurethane coatings and in stainless steel tanks
- › Not suitable for use on Aluminum, Magnesium and Zinc Silicate coatings

## APPLICATION AND USAGE

### General cleaning

- › Navaclean 802 is used as a solution made up in fresh water or sea water. If possible, we recommend to use fresh water. The efficient operating temperature varies and is depending upon the type of cargo residues which are to be cleaned.
- › Navaclean 802 can be applied by brush, and by direct injection method, but is mostly used by recirculation method.

### Pre-wash

- › Before cleaning tanks with Navaclean 802 it is recommended to pre-wash the cargo tanks with hot water 50 - 60°C
- › For Drying oils and Semi-Drying oils a prewash of the tanks with ambient water should be applied.

## PRODUCT CHARACTERISTICS

Appearance:	Clear liquid
Specific gravity:	1.06
Flash point:	None
pH-value at 20° C:	>12

### Corrosive action:

Metals: Avoid contact with aluminium, tin, zinc or their alloys.

Rubber: None

The information and recommendations given herein are believed to be accurate and reliable. However, since conditions of actual use are beyond our control, any recommendations or suggestions are made without any warranty and liability, expressed or implied.