PRODUCT INFORMATION

# NAVACLEAN 856 ECOCLEAN



# A WATER BASED MULTIPURPOSE CLEANER FOR CARGO TANKS

### **DESCRIPTION**

- > Removes oil or dirt from any surface
- > Natural citrus oil and advanced wetting agents makes this product a powerful high-quality cleaner and degreaser.
- > Available in 25/200/208 liter drums
- > Can be discharged according to Marpol V and IMO MEPC.1/Circ. 590

#### **FEATURES**

- > Numerous marine cleaning and degreasing applications
- > Engine room, galley, and deck general cleaning
- Low-toxic
- Nonflammable
- > Biodegradable
- > Pleasant and healthy environment
- Approved according to IMO MEPC.1/Circ. 590
- Complies to Marpol V

For detailed instructions on cargo hold cleaning please contact us at NAVADAN

A range of support application equipment is also available



#### **DIRECTION FOR USE**

## **Tank Cleaning**

> Cargo tank cleaning after mineral, animal, fish and vegetable oils. Hydrocarbon freeing after cleaning with hydrocarbon solvent based cleaners like Navaclean 888, Navaclean 818, etc.

# **Direct Injection Method**

This will require a solution strength between 0.5 and 1%.

#### **Recirculation Method**

> Use a solution strength between 0.5 and 2% The solution can be re-used until it is no longer effective.

# **Spot Cleaning**

- Depending upon the contamination Navaclean 856
   be sprayed undiluted or diluted down to 10% in water
   and allowed to soak on the area for 20 30 minutes.
   It must then be washed down with plenty water.
- > The efficiency is increased by using warm water up to 60°C both for cleaning and when rinsing the surfaces.

#### PRODUCT CHARACTERISTICS

Completely miscible with sea water and fresh water. Suitable for use on zinc-silicate coatings and most common metals. Limited application on epoxy coatings. The maximum concentration is 10% and a maximum temperature of 60°C.

Appearance: Light yellow liquid

Specific gravity: 1.00

Flash Point (PMCC): >80°C

pH-value (1% solution): 7

Corrosive action:

Metals: None

Rubber: May soften rubber

For special risks and safety regulations, please see our Safety Data Sheet